

It's  
PG Bison.

MELAWOOD  
SUPAMATT®

Silky smooth and luxurious, MelaWood SupaMatt® is for use in vertical applications only.

MelaWood SupaMatt® incorporates leading technology to help reduce the visibility of fingerprints under normal, day-to-day conditions.\*

\*PLEASE NOTE, as with other matt surfaces, visibility of oily finger marks and other oils and creams on the surface of the panel comes down to the volume of oil or cream transferred to the surface upon contact and cannot always be entirely concealed. With the right care and cleaning, this can be avoided or at the very least kept to a minimum.

## CLEANING INSTRUCTIONS

**ALWAYS AVOID HARSH HOUSEHOLD CLEANERS AND ABRASIVE MATERIALS AND CLEANING AGENTS**

Please see list of active ingredients in cleaners to be avoided on page 2

- Any spilt chemicals and liquids that can cause stains must be wiped away immediately, using a damp cloth and soapy solution. Repeat the process, as necessary.
- Do not overly wet the surface and always take care to prevent any moisture from penetrating any unprotected or exposed edges.
- For daily wiping down, always use a well rung out, damp, soft, lint-free cloth with clean water.
- For removing daily grime, always use a well rung out, damp, soft, lint-free cloth with a mild soap and water solution.
- For more stubborn marks or to remove drying marks and streaks, always use a well rung out, damp, soft, lint-free cloth with 1-part name brand window-cleaner to 1-part water dilution, drying off the last streaks with soft paper towel.
- For oily marks, use a dry or well rung out, damp, melamine foam\*\* (magic eraser sponge) with clean water.

\*\*Oakmont (formerly known as Weiman) Magic Eraser is our recommended example of melamine foam.



CUSTOMER SERVICE CENTRE 0860 579 196  
JOHANNESBURG 011 897 5200  
CAPE TOWN 087 357 7989  
DURBAN 087 350 0874  
EXPORTS 011 897 5200



pgbison.co.za



 **PG BISON**

It's  
PG Bison.

MELAWOOD  
SUPAMATT®



## CARE INSTRUCTIONS

- Utmost care should be taken when handling, machining and installing the product so as not to damage the surface.
- Always keep the protective film in place until installation is completed and all other service providers have finished their projects.
- The protective film should be removed within 6 months of completion of the job to avoid it ageing and becoming difficult to remove.

Never use any of the following cleaning agents on the matt surface:

- Abrasive cloths, scrubbing brushes, scrapers, scouring pads, steel wool or any other abrasive tool or material on the matt surface
- Scouring and abrasive agents such as abrasive powders
- Polish with abrasive compounds, washing powder, furniture cleaner and bleach
- Detergents with strong acids and acidic salts
- Steam cleaning equipment
- Solvents

**ALWAYS CHECK THE ACTIVE INGREDIENTS IN YOUR CLEANERS TO AVOID POTENTIALLY HARMFUL CHEMICALS DAMAGING THE SURFACE.**

### DO NOT USE

- acetone
- thinners
- methyl alcohol
- methyl ethyl ketone (MEK)
- ammonia
- amyl-acetate
- benzene
- butyl acetate
- butyl alcohol
- caustic soda
- cellusolve
- chlorinated solvents
- chloroform
- cresols/phenols
- dichloromethane
- ethyl-acetate
- glacial acetate acid
- halogenated solvents
- toluene
- xylene



CUSTOMER SERVICE CENTRE 0860 579 196  
JOHANNESBURG 011 897 5200  
CAPE TOWN 087 357 7989  
DURBAN 087 350 0874  
EXPORTS 011 897 5200



[pgbison.co.za](http://pgbison.co.za)



 **PG BISON**